

Full range on FlowCon E-JUST

FlowCon International can now introduce the next size of the FlowCon E-JUST, external adjustable flow control cartridge:

- E-JUST3.G.B

This new 2" E-JUST Cartridge will fit in FlowCon AB-bodies DN40 and DN50, which are available with either plugs or pressure/temperature plugs for verifying differential pressure range and the performance of the cartridge. The E-JUST3.G.B cartridge is available with flow rates from 3180-16100 l/hr (14.0-70.9 GPM) and in a dP range from 20-400 kPaD (2.9-58 psid).

Along with this new size E-JUST, FlowCon also expands the current range with an additional 3/4" E-JUST cartridge, i.e. E-JUST1.Y.R and E-JUST1.G.R (previously E-JUST1.Y.R). The new red E-JUST is developed to cover a current gap and will be available with flow rates between 276-825 l/hr (1.22-3.60 GPM) in the low dp range of 17-200 kPaD (2.5-29 psid). This cartridge will - like the rest of the 3/4" cartridges fit in FlowCon A, AB and ABV valve bodies, DN15-DN25.

The Widest Program

With the two new E-JUST cartridges, FlowCon International offers a complete range of external adjustable cartridges covering all flow rates from 100 l/hr to 17000 l/hr (0.44-74,8 GPM) in two main differential pressure ranges and in optional valve bodies from DN15 to DN50. For larger diameters up to DN150 FlowCon also carries the FlowCon SH valves which are external adjustable, but with a built-in diaphragm.

For more information please check the new FlowCon cartridge catalogue or the individual E-JUST tech note here on the FlowCon web-page.





DENMARK

DUBAI

SINGAPORE

USA

— www.flowcon.com

FlowCon International A/S flowcon@flowcon.com +45 58 50 52 30 FlowCon Int. ME, LLC me@flowcon.com +971 4 341 7767 FlowCon Int. Asia office asia@flowcon.com +65 6841 8849 FlowCon Americas, LLC usa@flowcon.com +1 704 599 4700